

IN THE CLAIMS:

Please amend claims 1, 6, 7, 10 and 11 as follows:

LISTING OF CURRENT CLAIMS

Claim 1. (Currently Amended) A windows-breaking emergency escape device ~~which comprises~~ comprising: a main body, a hammer and a supplementary power apparatus, ~~wherein~~ the hammer and the supplementary power apparatus are installed on the main body, ~~the a~~ front end of the hammer ~~extrudes from the~~
5 ~~protrudes from a~~ surface of the main body, ~~the improvement comprising that the~~ supplementary power apparatus further comprises a handler, a elastic component, a buckling component and a release button, wherein a groove is disposed on the main body for receiving the hammer, the elastic component is disposed between the hammer and the groove for providing a force to push the hammer outward, a circle
10 rim is disposed on the hammer, and the handler is pivoted on the main body, one end of the handler extends to form an extruding portion that contacts against the rim on the hammer, when ~~the a~~ user moves the handler, the hammer will be pushed inward to press the elastic component, the buckling component is pivoted and fixed firmly on the main body, one end of the buckling component contacts against the
15 release button, another end of the buckling component extrudes and extends into the groove that contains the hammer, when the hammer is pushed by the extruding portion of the handler to move backward and to push the elastic components to a certain position, the hammer will be held by the buckling component.

Claim 2. (Original) The windows-breaking emergency escape device according to claim 1, wherein the main body further comprises a cutter groove that contains a cutter.

Claim 3. (Original) The windows-breaking emergency escape device according to claim 2, wherein the width of the cutter groove is smaller than that of a child's finger.

Claim 4. (Original) The windows-breaking emergency escape device according to claim 1, wherein the cutter groove is disposed in a decline manner.

Claim 5. (Original) The windows-breaking emergency escape device according to claim 1, wherein the main body further comprises a lighting apparatus.

Claim 6. (Currently Amended) The windows-breaking emergency escape device according to claim 1, wherein the handler further comprises a hole that ~~can receive~~ receives a different type of screwdriver.

Claim 7. (Currently Amended) The windows-breaking emergency escape device according to claim 1, wherein the device further comprises a fix base that ~~can be~~ is placed in a proper location in the a car to hold the device.

Claim 8. (Original) The windows-breaking emergency escape device according to claim 1, wherein the handler is pivoted near a protruding portion of the main body.

Claim 9. (Original) The windows-breaking emergency escape device according to claim 1, wherein the main body further comprises an alarm.

Claim 10. (Currently Amended) The windows-breaking emergency escape device according to claim 5, wherein a penetrating hole is disposed on the ~~a~~ a case of the lighting apparatus near to a power outlet and a protruding portion is disposed on the corresponding place on the fix base so that the protruding portion ~~can engage~~ engages into the penetrating hole to power off the lighting apparatus.

Claim 11. (Currently Amended) The windows-breaking emergency escape device according to claim 7, wherein a penetrating hole is disposed on ~~the~~ a case of the lighting apparatus near to a power outlet and a protruding portion is disposed on the corresponding place on the fix base so that the protruding portion ~~can engage~~ engages into the penetrating hole to power off the lighting apparatus.